



Standard Package Components

- OS main unit
- Battery (BDC72)
- Battery charger (CDC77)
- Power Cable
- Lens cap
- Lens hood
- Tool pouch
- Precision screwdriver
- Lens brush
- Adjusting pin×2
- Silicon cloth
- Quick manual
- USB flash drive(Manual)
- Laser caution sign-board
- Carrying case
- Carrying strap

SPECIFICATIONS		
OS-201		
Telescope		
Magnification / Resolving power	30x / 2.5"	
Others	Length: 171mm (6.7in.), Objective aperture: 45mm (1.8in.) (48mm (1.9in.) for EDM), Image: Erect, Field of view: 1°30' (26m/1,000m), Minimum focus: 1.3m (4.3ft.), Reticle illumination: 5 brightness levels	
Angle measurement		
Display resolution	0.5" / 1" (0.0001 / 0.0002gon, 0.002 / 0.005mil)	
Accuracy (ISO 17123-3:2001)	1"	
Dual-axis compensator / Collimation compensation	Dual-axis liquid tilt sensor, working range: ±6' (±111mgon) / Collimation compensation available	
Distance measurement		
Laser output ^{*1}	Reflectorless mode: Class 3R / Prism/sheet mode: Class 1	
Measuring range (under average conditions ^{*2})	Reflectorless ^{*3}	0.3 to 800m (2,620ft.) / Under good conditions ^{*5} : 1,000m (3,280ft.)
	Reflective sheet ^{*4, *5}	RS90N-K: 1.3 ~ 500m, RS50N-K: 1.3 ~ 300m, RS10N-K: 1.3 ~ 100m
	Mini prism	1.3 to 500m (1,640ft.)
	One prism	1.3 to 5,000m (4.3 to 16,400ft.) / Under good conditions ^{*6} : 1.3 to 6,000m (19,680ft.)
Display resolution	Fine/Rapid measurement	0.0001m(0.001ft. / 1/16in.) / 0.001m (0.005ft. / 1/8in.) (selectable)
	Tracking/Road measurement	0.001m (0.005ft. / 1/8in.) / 0.01m (0.1ft. / 1/2in.) (selectable)
Accuracy ^{*2} (ISO 17123-4:2001) (D=measuring distance in mm)	Reflectorless ^{*3}	(2 + 2ppm x D) mm ^{*7}
	Reflective sheet ^{*4}	(2 + 2ppm x D) mm
	Prism	(1.5 + 2ppm x D) mm
Measuring time ^{*8}	Fine: 0.9s (initial 1.5s), Rapid: 0.6s (initial 1.3s), Tracking: 0.4s (initial 1.3s)	
OS, Interface and Data management		
Operating system	Windows Embedded Compact7	
Display / Keyboard	3.5inch, Transmissive TFT QVGA color LCD with LED backlight, Touch screen, Automatic brightness control / 29 keys with backlight	
Control panel location	On both faces (Face 2 is only touch screen display)	
Trigger key	On right instrument support	
Data storage	Internal memory	1GB internal memory (includes memory for program files)
	Plug-in memory device	USB flash memory
Interface	Serial RS-232C, USB2.0 (Type A / mini B)	
General		
Guide light ^{*9}	Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) ^{*2}	
Laser-pointer ^{*9}	Coaxial red laser using EDM beam	
Calendar / clock function	Yes	
Levels	Graphic	6'(inner circle)
	Circular level	10' / 2mm
Optical plummet	Magnification: 3x, Minimum focus: 0.3m (11.8in.) from tribrach bottom	
Laser plummet (option)	Red laser diode (635nm±10nm), Beam accuracy: <=1.0mm@1.3m, Class 2 laser product	
Tribrach	Detachable	
Dust and water protection	IP65 (IEC 60529:2001)	
Operating temperature ^{*9}	-20 to 60°C (-4 to 140°F)	
Size (with handle)	191(W)x190(D)x348(H)mm	
Instrument height	192.5mm from tribrach mounting surface	
	236mm +5/-3mm from tibrach bottom	
Weight with battery & tribrach	Approx. 5.7kg (12.3 lb.)	
Power supply		
Battery	BDC72	Li-ion rechargeable battery
Operating time (20°C)	BDC72	Approx. 20hours (single distance measurement every 30 seconds)

^{*1} IEC60825-1:Ed 2.0:2007 / FDA CDRH 21 CFR Part 1040.10 and 11
^{*2} Average conditions: Slight haze, visibility about 20km (12 miles), sunny periods, weak scintillation.
^{*3} Fine mode. With Kodak Gray Card White Side (90% reflective). When brightness on measured surface is 30,000 lx. or less. Reflectorless range/accuracy may vary according to measuring objects, observation situations and environmental conditions.
^{*4} When the measuring beam's incidence angle is within 30° in relation to the reflective sheet target.
^{*5} Measuring range in temperatures of -30 to -20°C (-22 to -4°F) with Low Temperature models and 50 to 60°C (122 to 140°F) with High Temperature models: RS90N-K: 1.3 to 300m (4.3 to 980ft.), RS50N-K: 1.3 to 180m (4.3 to 590ft.), RS10N-K: 1.3 to 60m (4.3 to 190ft.)
^{*6} Good conditions: No haze, visibility about 40km (25 miles), overcast, no scintillation.
^{*7} Measuring range:0.3 to 200m
^{*8} Typical, under good conditions. Reflectorless measurement time may vary according to measuring objects, observation situations and environmental conditions.
^{*9} The laser-pointer and the guide light do not work simultaneously.
^{*10} Low Temperature models:-30 to 50 °C (-22 to 122°F) is available on built-to-order basis.

- Specifications may vary by region and are subject to change without notice.
- Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license.
- Other trademarks and trade names are those of their respective owners.

Your local Authorized Dealer is:

OS-200series
Onboard Station



For professionals like you

- High performance EDM for rapid, repeatable measurements
- Modern, intuitive onboard MAGNET® Field software
- Convenient EDM trigger key
- Reflectorless laser measurement

